

## Safety Data Sheet according to Regulation (EC) No. 453/2010

according to Regulation (EC) No. 453/2010 Gasmixture: Ar + CO2 Date of issue: 29/11/2011 Revision date: 20/04/2015 140A

Version: 2.0



#### Warning

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
SDS no :	140A
1.2. Relevant identified uses of the substa	nce or mixture and uses advised against
Relevant identified uses :	Industrial and professional. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use. Contact supplier for more information on uses.
Uses advised against :	Consumer use.
1.3. Details of the supplier of the safety da	ta sheet
Company identification :	IJSFABRIEK STROMBEEK
	Broekstraat, 70
	B-1860 Meise Belgique-Belgie
	32 2 272 41 34
	info@ysfab.be
1.4. Emergency telephone number	
Emergency telephone number :	Tel : +32 2 272 41 34

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Gases under pressure : Compressed gas

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified as dangerous substance / mixture.

2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)

# : GHS04 : Warning

Signal word (CLP) Hazard statements (CLP)

: H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

- Storage : P403 - Store in a well-ventilated place.

#### 2.3. Other hazards

IJSFABRIEK STROMBEEK
Broekstraat, 70 B-1860 Meise Belgique-
Belgie
32 2 272 41 34

H280



#### : Asphyxiant in high concentrations.

#### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substance : Not applicable

#### 3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Argon	(CAS No) 7440-37-1 (EC no) 231-147-0 (EC index no) (REACH-no) *1	>=80	Not classified	Press. Gas (Comp.), H280
Carbon dioxide	(CAS No) 124-38-9 (EC no) 204-696-9 (EC index no) (REACH-no) *1	<=20	Not classified	Press. Gas (Liq.), H280

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*2: Registration deadline not expired.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

Full text of R-phrases see section 16. Full text of H-statements see section 16.

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

: Adverse effects not expected from this product.
: Adverse effects not expected from this product.
: Ingestion is not considered a potential route of exposure.
d effects, both acute and delayed
<ul> <li>In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Refer to section 11.</li> </ul>
edical attention and special treatment needed
: None.

#### **SECTION 5: Firefighting measures**

5.1. Extinguishing media		
- Suitable extinguishing media	: Water spray or fog.	
- Unsuitable extinguishing media	: Do not use water jet to extinguish.	
5.2. Special hazards arising from the substance or mixture		
Specific hazards	: Exposure to fire may cause containers to rupture/explode.	
Hazardous combustion products	: None.	



Specific methods	<ul> <li>Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.</li> <li>If possible, stop flow of product.</li> <li>Use water spray or fog to knock down fire fumes if possible.</li> <li>Move containers away from the fire area if this can be done without risk.</li> </ul>
Special protective equipment for fire fighters	<ul> <li>Use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.</li> <li>Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.</li> <li>Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.</li> </ul>

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

	<ul> <li>Try to stop release.</li> <li>Evacuate area.</li> <li>Monitor concentration of released product.</li> <li>Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.</li> <li>Ensure adequate air ventilation.</li> <li>Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.</li> <li>Act in accordance with local emergency plan.</li> <li>Stay upwind.</li> </ul>			
Environmental precautions				
	: Try to stop release.			
Methods and material for containment and cleaning up				
	: Ventilate area.			
Reference to other sections				

#### <u>6.4.</u> Reference to other sections

: See also sections 8 and 13.

#### **SECTION 7: Handling and storage**

#### Precautions for safe handling <u>7.1.</u>

Safe use of the product

<u>6.2.</u>

<u>6.3</u>.

: The substance must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not breathe gas. Avoid release of product into atmosphere.



Safe handling of the gas receptacle :	Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect cylinders from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. Containers should be stored in the vertical position and properly secured to prevent them from
7.2. Conditions for safe storage, including	falling over. any incompatibilities
:	Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.
7.3. Specific end use(s)	

: None.

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Carbon dioxide (124-38-9)			
OEL : Occupational Exposure Limits			
Belgium	TWA (BE) OEL 8h [mg/m3]	9131 mg/m <sup>3</sup>	
	TWA (BE) OEL 8h [ppm]	5000 ppm	
	STEL (BE) OEL 15min [mg/m3]	54784 mg/m <sup>3</sup>	
	STEL (BE) OEL 15min [ppm]	30000 ppm	

DNEL (Derived-No Effect Level) : No data available.

PNEC (Predicted No-Effect Concentration) : No data available.

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

:	Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available).
	Oxygen detectors should be used when asphyxiating gases may be released. Consider work permit system e.g. for maintenance activities.

#### 8.2.2. Individual protection measures, e.g. personal protective equipment

: A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.



Eye/face protection	: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection.
Skin protection	
- Hand protection	: Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk.
- Other	: Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
Respiratory protection	: Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Thermal hazards	: None necessary.
8.2.3. Environmental exposure controls	

: Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance

Physical state at 20°C / 101.3kPa : Gas . : Mixture contains one or more component(s) which have the following colour(s): Colour Colourless. Odour Odourless. : Odour threshold : Odour threshold is subjective and inadequate to warn of overexposure. pH value : Not applicable for gas-mixtures. Molar mass : Not applicable for gas-mixtures. Melting point : Not applicable for gas-mixtures. Boiling point : Not applicable for gas-mixtures. Flash point : Not applicable for gas-mixtures. Evaporation rate (ether=1) : Not applicable for gas-mixtures. Flammability range : Non flammable. Vapour pressure [20°C] : Not applicable. Vapour pressure [50°C] : Not applicable. Relative density, gas (air=1) : Heavier than air. : Solubility in water of component(s) of the mixture : Solubility in water • Argon: 67,3 mg/l • Carbon dioxide: 2000 mg/l Completely soluble. : Not applicable for gas-mixtures. Partition coefficient n-octanol/water [log Kow] Auto-ignition temperature : Non flammable. Viscosity [20°C] : Not applicable. **Explosive Properties** : Not applicable. **Oxidising Properties** : Not applicable. <u>9.2.</u> Other information Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

#### **SECTION 10: Stability and reactivity**



<u>10.1.</u>	Reactivity	
		: No reactivity hazard other than the effects described in sub-sections below.
<u>10.2.</u>	Chemical stability	
		: Stable under normal conditions.
<u>10.3.</u>	Possibility of hazardous reactions	
		: None.
<u>10.4.</u>	Conditions to avoid	
		: None under recommended storage and handling conditions (see section 7)
<u>10.5.</u>	Incompatible materials	
		: For additional information on compatibility refer to ISO 11114.
<u>10.6.</u>	Hazardous decomposition products	
		: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

#### **SECTION 11: Toxicological information**

11.1. Information on toxicological effects	
Acute toxicity	: No toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Assessment

: Classification criteria are not met.

Argon (7440-37-1)		
EC50 48h - Daphnia magna [mg/l]	No data available.	
EC50 72h - Algae [mg/l]	No data available.	
LC50 96 h - Fish [mg/l]	No data available.	
Carbon dioxide (124-38-9)		
EC50 48h - Daphnia magna [mg/l]	No data available.	
EC50 72h - Algae [mg/l]	No data available.	
LC50 96 h - Fish [mg/l]	No data available.	

#### 12.2. Persistence and degradability

#### Assessment

: No data available.

#### 12.3. Bioaccumulative potential

#### Assessment

: No data available.

#### 12.4. Mobility in soil



#### Gasmixture: Ar + CO2

SDS Ref.: 140A

Assessment	: No data available.
12.5. Results of PBT and vPvB assess	ment
Assessment	: Not classified as PBT or vPvB.
12.6. Other adverse effects	
Effect on ozone layer	: None.
Effect on the global warming	: Contains greenhouse gas(es) not covered by Regulation (EC) 842/2006.
13.1. Waste treatment methods	
13.1. Waste treatment methods	Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded.
	Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org for more guidance on suitable disposal methods.
List of hazardous waste codes (from Commission Decision 2001/118/EC)	: 16 05 05: Gases in pressure containers other than those mentioned in 16 05 04.
13.2. Additional information	
13.2. Additional information	

#### **SECTION 14: Transport information**

14.1. UN number			
UN-No.	: 1956		
14.2. UN proper shipping name	. 1920		
Transport by road/rail (ADR/RID)	: COMPRESSED GAS, N.O.S. (	Argon, Carbon dioxide)	
Transport by air (ICAO-TI / IATA-DGR)	: Compressed gas, n.o.s. (Argor	, Carbon dioxide)	
Transport by sea (IMDG)	: COMPRESSED GAS, N.O.S. (	Argon, Carbon dioxide)	
14.3. Transport hazard class(es)			
Labelling	2		
	2.2 : Non-flammable, non-toxic	gases	
Transport by road/rail (ADR/RID)			
Class	: 2		
Classification code	: 1A		
Hazard identification number	: 20		
Tunnel Restriction	: E - Passage forbidden through	tunnels of category E	
Transport by air (ICAO-TI / IATA-DGR)			
Class / Div. (Sub. risk(s))	: 2.2		
Transport by sea (IMDG)			
Class / Div. (Sub. risk(s))	: 2.2		
JJSFABRIEK STROMBEEK Broekstraat 70, B-1860 Meise Belgigue-	EN (English)	SDS Ref.: 140A	7/9



SDS Ref.: 140A

Emergency Schedule (EmS) - Fire	: F-C	
Emergency Schedule (EmS) - Spillage	: S-V	
14.4. Packing group		
Transport by road/rail (ADR/RID)	: Not applicable	
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable	
Transport by sea (IMDG)	: Not applicable	
14.5. Environmental hazards		
Transport by road/rail (ADR/RID)	: None.	
Transport by air (ICAO-TI / IATA-DGR)	: None.	
Transport by sea (IMDG)	: None.	
14.6. Special precautions for user		
Packing Instruction(s)		
Transport by road/rail (ADR/RID)	: P200	
Transport by air (ICAO-TI / IATA-DGR)		
Passenger and Cargo Aircraft	: 200	
Cargo Aircraft only	: 200	
Transport by sea (IMDG)	: P200	
Special transport precautions	<ul> <li>Avoid transport on vehicles where the load space is not separated from the driver's compartment.</li> <li>Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.</li> <li>Before transporting product containers: <ul> <li>Ensure there is adequate ventilation.</li> <li>Ensure that containers are firmly secured.</li> <li>Ensure cylinder valve is closed and not leaking.</li> <li>Ensure valve outlet cap nut or plug (where provided) is correctly fitted.</li> </ul> </li> </ul>	
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		

: Not applicable

#### **SECTION 15: Regulatory information**

15.1. Safety, health and environme	ntal regulations/legislation specific for the substance or mixture
Seveso directive 96/82/EC	: Not covered.
National regulations	
National legislation	: Ensure all national/local regulations are observed.
Water hazard class (WGK)	: -
15.2. Chemical safety assessment	
	: A CSA does not need to be carried out for this product.
SECTION 46: Other information	
SECTION 16: Other information	

: Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.



Training advice Further information : Receptacle under pressure.

: This Safety Data Sheet has been established in accordance with the applicable European Union legislation. Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP / (EC) 1999/45 DPD.

Full text of R-, H- and EUH-phrases

Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H280	Contains gas under pressure; may explode if heated

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.